




UNIVERSITY OF
BIRMINGHAM

SCHOOL OF
PHYSICS AND
ASTRONOMY

University of Birmingham EICROOT simulation effort

P.P. Allport, L. Gonella, P. Ilten, P.G. Jones, P.R. Newman,
H. Wennlöf

30/4 -2020



Introduction


- Baseline performance studies for both the central and forward regions of a Si+TPC and an all-Si tracker design
- Studies have covered:
 - Central region (i.e. barrel)
 - Forward/backward regions (i.e. disks)
 - Interface region between barrel and disks
 - Si+TPC compared to all-silicon
- Figures of merit for studies:
 - Relative momentum resolution
 - Transverse and longitudinal pointing resolutions
- Highlights covered in this talk. Details available in full report

Contents

Table of contents	ii
1 Introduction	3
2 Experimental setup	5
3 Results	7
3.1 Comparison no SVT/SVT+TPC	7
3.2 Barrel pixel size	8
3.3 Barrel layout studies	9
3.4 Radiation length scan	11
3.5 Time-stamping layer thickness and pixel size	11
3.6 Disks, varying pixel sizes	12
3.7 Innermost disk position	16
3.8 Different inner barrel length, with disks	17
3.9 Replacing gas TPC with silicon layers and disks	20
3.9.1 Different silicon layouts	20
3.9.2 Different silicon replacement outer radius	24
4 Conclusions and outlook	30
Appendix A Theoretical background	31
A.1 Particle interactions	31
A.1.1 Radiation length	31
A.1.2 Multiple scattering	31
A.2 Detector properties	32
A.2.1 Spatial resolution of segmented detector	32
A.2.2 Pointing resolution	33
A.2.3 Relative momentum resolution	34
Appendix B Fit interval trimming and comparison with eRD16	36
Appendix C Further gas TPC replacement studies	38
C.1 Different silicon layouts	38
C.1.1 Comparison of two silicon layers and five silicon layers	39
C.2 Different silicon replacement outer radius	40
Appendix D Area comparison to the ALICE ITS Upgrade	42
References	43


Silicon vertex tracker + TPC: baseline layout

- Sketch of the simulated silicon vertex tracker, with surrounding TPC
 - The beampipe runs through the centre of the detector, but is not shown in the figure
 - 5 barrel layers, 7 disks per side
 - TPC inner/outer radius: 225/775 mm
 - TPC length = 1960 mm




Simulation parameters used

- Starting point: BeAST tracker
 - Radii of barrel layers adjusted to be consistent with ALICE ITS distances between layers (minimum distance between outer layers is 46.2 mm)
- Beampipe
 - 18 mm radius in central region (± 400 mm), 0.8 mm thick beryllium
 - 20 mm radius aluminium further out
- TPC parametrisation default EICROOT one (conservative):
 - Transverse dispersion : 15.00 $\mu\text{m}/\sqrt{D[\text{cm}]}$
 - Transverse intrinsic resolution : 200.00 μm
 - Longitudinal dispersion : 1.00 $\mu\text{m}/\sqrt{D[\text{cm}]}$
 - Longitudinal intrinsic resolution: 500.00 μm
 - Vertical pad size : 0.50 cm



Barrel simulations


- Five layers
 - Two inner, two outer + time-stamping layer (see details on slide 7)
- Simulations studies performed
 - Pixel size
 - Number of layers
 - Radiation length scan
 - Time-stamping layer X/X_0 and pixel size
- Parameters used:
 - Particle: π^+
 - Transverse momentum range: 0 to 5 and 0 to 50 GeV/c
 - Pseudorapidity range: $-0.5 \leq \eta \leq 0.5$
 - Default pixel size: $20 \times 20 \mu\text{m}^2$
 - Material budget: 0.3/0.8 % X_0 inner/outer layers, 1.6 % time-stamping layer
 - Magnetic field: uniform 1.5 T




Barrel simulations: number of layers

- Different number of layers tested, keeping the innermost and outermost layers the same at a radius of 23.4 mm and 133.8 mm respectively


Relative momentum resolution




Transverse pointing resolution



Relative momentum resolution




Transverse pointing resolution



Time-stamping layer - details


- Adding time-stamping capability to the vertex and tracking detector would allow to **time-stamp bunch crossings** and thus **keep track of beam polarisation**
- With a bunch-crossing frequency of 112.6 MHz, a **time resolution <9 ns is needed**
- This might require a sensor with a **larger pixel size and power consumption** than those required for vertex and tracking measurements
- A dedicated time-stamping layer is therefore studied
- This layer is placed at a radius of 180.0 mm
- Investigations are done altering **thickness** (proportional to power consumption) and **pixel size** of the layer
- For thickness studies, a pixel size of $20 \times 20 \mu\text{m}^2$ is used. For pixel size studies, the thickness is kept at 1.6 % X_0




Addition of time-stamping layer - results

■ Different thicknesses:

Relative momentum resolution




Transverse pointing resolution




■ Different pixel sizes:

Relative momentum resolution




Transverse pointing resolution





Simulations of disks – pixel sizes



- Simulations have studied two configurations, with either 7 or 5 disks per side
 - First disk 5 mm from inner layer edge (i.e. 140.0 mm from centre)
 - Remaining disks equidistant between 425.0 mm and 1210.0 mm
 - Radius of first disk: 82.6 mm
 - Radius of remaining disks: 190.0 mm
- Parameters used:
 - Particle: e-
 - Momentum range: 0 to 50 GeV/c
 - Pseudorapidity: $\eta = 3$
 - Material budget: 0.3 % X_0 per disk
 - Magnetic field: uniform 1.5 T and 3 T
- Impact of pixel size investigated





Disk pixel sizes - results



7 disks, 1.5 T



7 disks, 3 T




5 disks, 3 T





Barrel/disk interface region simulations

- Studies have looked at
 - Innermost disk position (at $\eta = 3$)
 - Length of inner barrel layers (at range of pseudorapidities)
- Length of inner barrel layer study presented here
- Innermost disk always 5 mm from inner barrel edge
- Parameters
 - Particle: e^-
 - Momentum range: 0 to 50 GeV/c
 - Pseudorapidity range: $0 \leq \eta \leq 2.5$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: 1.5 T
- Results show that 270 mm long inner barrel is best

Relative momentum resolution vs η




Transverse pointing resolution vs η




Silicon and gas TPC compared to all-silicon layouts

- Various all-silicon layouts tested. Details can be found in Section 3.9 here:
<http://cern.ch/go/xKk6>
 - Key layouts are shown schematically on the next slide
- Parameters used:
 - Particle: e-
 - Momentum range: 0 to 50 GeV/c
 - Pseudorapidity range: $0 \leq \eta \leq 2.5$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: uniform 1.5 T
 - Layer thickness in “TPC replacement”: $0.8 \% X_0$




Key layouts and their aliases

2+2 layers, long




All-silicon layouts - results

Relative momentum resolution vs p




Relative momentum resolution vs η



- Large disk coverage is important to keep resolution at higher η
- All-silicon layout can outperform Si+gas at $p \geq 5$ GeV/c
- Pointing resolutions do not change much between layouts, apart from where layers are missed

Decreasing radius study


- Goal: investigate performance of Si+gas and all-Si when outer radius is decreased
- Best-performing all-silicon layout used (“5 layers, short, optimised disks”, see slide 13). Outer radius decreased, layers kept equidistant
- Studies are made in central and forward regions for the all-silicon layouts, and in the central region for silicon+gas layouts
- The central region study comparing silicon+gas with all-silicon is presented here
- Parameters used:
 - Particle: e^-
 - Momentum range: 0 to 30 GeV/c
 - Pseudorapidity range: $0 \leq \eta \leq 1$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: uniform 1.5 T
 - Baseline barrel used (5 layers)



Decreasing radius study

■ Outer radii tested:


- 409.8 mm,
- 500.0 mm
- 600.0 mm
- 775.0 mm




All-silicon layout superimposed with gas TPC

Decreasing radius study - results

Relative momentum resolution




Transverse pointing resolution



- Colours correspond to radii. Solid line with circular markers indicates all-silicon, and dashed line with square markers indicates silicon+gas TPC
- All-silicon layout relative momentum resolution deteriorates slower with increasing momentum
- The smaller the radius, the better the all-silicon compared to Si+gas


Conclusions

- Best layout, indicated from these simulations:
 - Two inner layers (two to keep redundancy)
 - Two outer layers (two to help in track reconstruction)
 - Optional time-stamping layer **is not severely detrimental** to resolutions
 - **Not necessary for tracking**, but potentially helps detection in other ways by keeping track of bunch crossings
 - Seven silicon disks in forward and backward regions
 - First disk as close as possible to interaction point, inside barrel
 - Remaining disks equidistant
 - 5 disks show similar performance, but 7 provide more coverage
- Pixel size needs to be kept **small**; current baseline $20 \times 20 \mu\text{m}^2$
 - Smaller is better, as long as power density can be kept low
- All-silicon layouts can match silicon+gas TPC layouts above a few GeV/c, and outperform them at higher momenta
- If **smaller radius** is desired, it appears better to replace gas TPC with silicon layers



More EICROOT studies for Pavia meeting


- Simulate best layouts with
 - New beampipe configuration (i.e. 31 mm radius)
 - 1.5 T and 3 T magnetic field comparison in barrel region
 - More realistic TPC, as simulated by eRD6
- Impact of adding a third inner layer (after discussion with Jin Huang), to be able to reconstruct even if a layer is missed






Backup/more studies

Note: still not all the results. See report for complete summary; <http://cern.ch/go/xKk6>




Comparison no SVT/SVT+TPC

- Parameters used:
 - Particle: π^+
 - Momentum range: 0 to 50 GeV/c
 - Pseudorapidity range: $-0.5 \leq \eta \leq 0.5$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: uniform 1.5 T
 - Baseline barrel used (5 layers)
- Goal:
 - See that SVT is necessary
- See Section 3.1 in report for details




(a) Relative momentum resolution.




(b) Transverse pointing resolution.

Figure 3: Relative momentum resolution and transverse pointing resolution, comparing having a standard barrel with a $20 \times 20 \mu\text{m}^2$ pixel size with a TPC outside, and just having a TPC extending all the way to the same innermost radius as the barrel.




Barrel pixel size

- Parameters used:
 - Particle: π^+
 - Momentum range: 0 to 5 GeV/c
 - Pseudorapidity range: $-0.5 \leq \eta \leq 0.5$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: uniform 1.5 T
 - Baseline barrel used (5 layers)
- Goal:
 - Investigating effect of barrel pixel size on resolutions
- See Section 3.2 in report for details



(a) Relative momentum resolution.



(b) Transverse pointing resolution.

Figure 4: Relative momentum resolution and transverse pointing resolution for different pixel sizes in the silicon vertex tracker barrel.

Innermost disk position

- Parameters used:
 - Particle: e-
 - Momentum range: 0 to 50 GeV/c
 - Pseudorapidity: $\eta = 3$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: uniform 3 T
- Goal:
 - Investigating effect of changing the innermost disk position
- See Section 3.7 in report for details
- Main conclusion is that as long as a disk is hit, it should be as close to the interaction point as possible.






Figure 13: Relative momentum resolution and pointing resolutions for a 7 disk layout, with varying innermost disk positions.




All-silicon, comparing 2 layers and 5 layers

- Goal:
 - Investigate difference between 2 layer TPC replacement, and 5 layer TPC replacement
 - 5 layers would help with tracking
- See Section C.1.1 in report for details



(a) Relative momentum resolution.



(b) Transverse pointing resolution.


Figure 33: Relative momentum resolution and transverse pointing resolution versus momentum for 2 and 5 layers in the TPC replacement silicon barrel.

- Result: not severely detrimental to have 5 layers instead of 2


All-silicon outer radius studies

- Parameters used:
 - Particle: e^-
 - Momentum range: 0 to 30 GeV/c
 - Pseudorapidity range: $0 \leq \eta \leq 1$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: uniform 1.5 T
 - Baseline barrel used (5 layers)

- Goal:
 - Investigating effect of decreasing radius of all-silicon, compared to the baseline silicon+gas TPC layout
- See Section 3.9.2 in report for details



(a) Relative momentum resolution versus momentum.




(b) Relative momentum resolution versus pseudorapidity.

Figure 23: Relative momentum resolution versus momentum and pseudorapidity for different silicon TPC replacement outer radii, in the momentum range 0 to 30 GeV/c and pseudorapidity range $0 \leq \eta \leq 1$.


All-silicon outer radius studies

- Results:
 - At low momenta, Si+gas is always better
 - At increasing momentum, Si+gas loses performance faster than all-silicon.
 - At momenta above 6 GeV/c, all-silicon outperforms Si+gas
- See Section 3.9.2 in report for details




All-silicon outer radius studies – forward regions

- Parameters used:
 - Particle: e-
 - Momentum range: 0 to 50 GeV/c
 - Pseudorapidity range: $1 \leq \eta \leq 2.5$
 - Pixel size: $20 \times 20 \mu\text{m}^2$
 - Magnetic field: uniform 1.5 T
 - Baseline barrel used (5 layers)
- Goal:
 - Investigating effect of decreasing radius of all-silicon, compared to the baseline silicon+gas TPC layout, in forward regions
- See Section 3.9.2 in report for details



(a) Relative momentum resolution.



(b) Transverse pointing resolution.

Figure 24: Relative momentum resolution and transverse pointing resolution versus momentum for different silicon TPC replacement outer radii, with optimised disk layout. Forward regions ($1 \leq \eta \leq 2.5$).

